

## NSR-9614XL

### Metal Multi-Function Duty / Personal-Size Flashlight Rechargeable

<b>MARKET APPLICATIONS</b>	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
<b>DESCRIPTION</b>	The NSR-9614XL rechargeable aircraft-grade aluminum LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. Utilizing a CREE® LED, the 9614XL has an impressive runtime of 6.5 hours in full-brightness mode. The 650 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 325 meters. The 9614XL has a dual button design, one located on the waterproof body of the light, and the other in the tail cap. Both buttons operate in tandem with each other. Meets requirements of NFPA-1971-8.6 (2013).
<b>CASE MATERIAL</b>	Aircraft-grade 6061-T6 Aluminum with Type III Hard Anodized Finish - Black
<b>DIMENSIONS</b>	Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)
<b>WEIGHT</b>	Weight: 12.8 oz. (363 g) with battery installed.
<b>LENS</b>	Unbreakable polycarbonate with scratch resistant coating.
<b>LIGHT SOURCE</b>	Cree® LED. Impervious to shock with a 50,000 + hour lifetime.
<b>LIGHT OUTPUT</b>	High-Brightness - 650 lumens • Medium-Brightness - 200 lumens • Low-Brightness 50 lumens
<b>ON/OFF</b>	Single Body Switch & Single Tail Switch (Tandom Functionality) - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe
<b>RUN-TIME</b>	High-brightness - 6.5 hours • Medium-brightness - 9 hours • Low-brightness - 12 hours
<b>BATTERY</b>	2-cell, 3.7 Volt Lithium-ion battery pack.
<b>CHARGING</b>	Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• CREE® LED technology – 50,000 + hours LED life</li> <li>• Momentary or constant-on plus 3 brightness levels &amp; strobe</li> <li>• Sharp focused beam</li> <li>• Aircraft-grade 6061-T6 aluminum housing/tail-cap/bezel</li> <li>• Type III hard anodized finish</li> <li>• Non-slip grip</li> <li>• Body &amp; tail switch</li> <li>• Waterproof</li> <li>• Impact &amp; chemical resistant</li> <li>• Meets requirements of NFPA-1971-8.6 (2013)</li> <li>• Serialized for personal identification</li> <li>• Powered by rechargeable Lithium-ion battery (included)</li> <li>• Includes wall or vehicle mounted charger as well as AC and DC power supply and anti-roll ring</li> </ul>
<b>WARRANTY</b>	Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

**APPROVALS**



**OPTIONAL ACCESSORIES**

5 Bank Charger, Direct Wire Kit, USB Charging Cable, Red, Yellow & Blue Safety Cones

FL1 STANDARD	HIGH	MEDIUM	LOW
	650 LUMENS	200 LUMENS	50 LUMENS
	6h 30 min	9h	12h
	325m	235m	118m
	23976cd	12075cd	6200cd
	2m / 1m		

