

PRODUCT FACT SHEET

STRION® LED

HIGH PERFORMANCE RECHARGEABLE FLASHLIGHT

MARKET

APPLICATIONS: Premium Professional Light - Law Enforcement, Industrial, Security, Outdoor, Consumer

DESCRIPTION: Ultra compact & powerful, the Strion® LED rechargeable flashlight offers 3 microprocessor

controlled variable intensity modes, strobe mode and the latest in power LED technology. The combination of rechargeable batteries and high power LED results in one of the lowest operating

costs of any flashlight made.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Length: 5.90 in. (14.99 cm) Head Diameter: 1.25 in. (3.18 cm)

Barrel Diameter: 0.95 in. (2.41 cm) Diameter at Tri-Lobe Anti-Roll Flange: 1.35 in. (3.43 cm)

WEIGHT: 5.2 oz (148 grams) with battery

LENS: Borofloat High Temperature Glass. Gasket sealed.

LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

1375 LUMENS 12,000 cd

ON/OFF: Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable

intensity or strobe mode.

See chart. All claims to 10% of initial lumen output. Strobe: 6.5 continuous hours.

BATTERY: Lithium Ion with on-board safety control circuit, 3.63V, 2600mAh, rechargeable up to 1000 times.

CHARGING: Fits existing Strion® chargers.

Clamp style charge holder with digital control circuit that prevents overcharge.

Fully recharges battery in 3.5 hours and charges battery in product.

Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.

FEATURES: High power LED for extreme brightness.

IPX4 rated design; water resistant operation.

2 meter impact resistance tested.

LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position.

Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty.


APPROVALS: (Meets applicable European Community directives.

(BC) CEC Compliant

OPTIONAL

ACCESSORIES: Color Filters, Safety Wands, Holster, Rail Mount, Piggyback® Charger, 6 Unit Bank Charger.

1	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	31/2	375 LUMENS	175 LUMENS	80 LUMENS
RUNTIME	0	2h 30min	4h 45min	9h 30 min
DISTANCE		219m	161m	113m
INTENSITY		12,000cd	6,500cd	3,200cd



All performance claims tested to ANSI/PLATO FL1-2016 Standard

Issued: 10/27/2008 Revised: 05/08/2019 Rev: 11