

© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, ONLINEREPAIR.AKRONBRASS.COM

USE PARKER O-LUBE ON ALL

O-RINGS AND MATING SURFACES

Chg.

08

09

Date

08-17


10-17

UNLESS OTHERWISE NOTED.

- USE PERMABOND LM113 OR ∕1∖ LOCTITE 222.
- 2 USE MOBILITH SHC 460.
- 3DIMPLE AT ASSEMBLY.
- 6 ALIGN BALL IN HOLE. TIGHTEN PLUG UNTIL TOUCHES BALL. THEN BACK OUT PLUG 1/4-1/2 TURN.
- ∕7∖ TIGHTEN UNTIL SLIGHT DRAG IS ON ITEM (42)
- /9\ TIGHTEN UNTIL ALL END PLAY IS ELIMINATED. SHAFT ASSEMBLY MUST STILL SPIN FREELY. DO NOT OVERTIGHTEN.
- 10. USE LOW-TEMP LUBRIPLATE.
- 1 USE NEVER SEEZ MARINERS CHOICE.
- 12 USE PRIMER T AND PERMABOND HH120 OR LOCTITE 277.
- <u>∕1</u>3 USE PARKER O-LUBE.
- 14 THOROUGHLY CLEAN THREADS OF PLUG AND MATING PART AND APPLY LOCTITE 425.
- △15 AS SPECIFIED.
- 16 MAY BE SUPPLIED WITH STORZ FITTING WHEN SPECIFIED.
- $\cancel{1}$ OPTIONAL DRAIN VALVE LOCATION, USE PERMABOND LH050 OR LOCTITE 592.
- 18 TIGHTEN TO 50-55 IN-LBS.

Parts List Sheet:

124912



WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Scene Star Lights carry a (6) year warranty. Weldon products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.

© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, **ONLINEREPAIR.AKRONBRASS.COM**

∕2∖

(43)

(34)

(47)(29)(23)(24

/2`

 $(33)^2$

(32)

 Chg.
 Date

 08
 08-17

 09
 10-17

ASSEMBLY NOTES: USE PARKER O-LUBE ON ALL

O-RINGS AND MATING SURFACES

UNLESS OTHERWISE NOTED.

- LOCTITE 222.
- 2 USE MOBILITH SHC 460.
- 3 DIMPLE AT ASSEMBLY.
- ALIGN BALL IN HOLE. TIGHTEN PLUG
 UNTIL TOUCHES BALL. THEN BACK
 OUT PLUG 1/4-1/2 TURN.
- $\overrightarrow{7}$ TIGHTEN UNTIL SLIGHT DRAG IS ON ITEM $\overrightarrow{42}$.
- TIGHTEN UNTIL ALL END PLAY IS ELIMINATED. SHAFT ASSEMBLY MUST STILL SPIN FREELY. DO NOT OVERTIGHTEN.
- 10. USE LOW-TEMP LUBRIPLATE.
- $\cancel{11}$ USE NEVER SEEZ MARINERS CHOICE.
- ✓12 USE PRIMER T AND PERMABOND HH120OR LOCTITE 277.
- 13 USE PARKER O-LUBE.
- AND MATING PART AND APPLY LOCTITE 425.
- $\cancel{15}$ AS SPECIFIED.
- 16 MAY BE SUPPLIED WITH STORZ FITTING WHEN SPECIFIED.
- ✓ ↑ OPTIONAL DRAIN VALVE LOCATION, USE PERMABOND LH050 OR LOCTITE 592.
- 18 TIGHTEN TO 50-55 IN-LBS.

23

(29)


47

(30)

Parts List Sheet:

124912

D47460



have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products. © 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, ONLINEREPAIR.AKRONBRASS.COM

Chg. Date 08 08-17 09 10-17

ASSEMBLY NOTES: USE PARKER O-LUBE ON ALL

O-RINGS AND MATING SURFACES


UNLESS OTHERWISE NOTED.

- 1 USE PERMABOND LM113 OR LOCTITE 222.
- 2 USE MOBILITH SHC 460.
- <u>J</u> DIMPLE AT ASSEMBLY.
- 6 ALIGN BALL IN HOLE. TIGHTEN PLUG UNTIL TOUCHES BALL. THEN BACK OUT PLUG 1/4-1/2 TURN.
- $\angle 7$ TIGHTEN UNTIL SLIGHT DRAG IS ON ITEM (42)
- TIGHTEN UNTIL ALL END PLAY IS ELIMINATED. SHAFT ASSEMBLY MUST STILL SPIN FREELY. DO NOT OVERTIGHTEN.
- <u>10</u> USE LOW-TEMP LUBRIPLATE.
- 11 USE NEVER SEEZ MARINERS CHOICE.
- 12 USE PRIMER T AND PERMABOND HH120 OR LOCTITE 277.
- <u>1</u>3 USE PARKER O-LUBE.
- 14 THOROUGHLY CLEAN THREADS OF PLUG AND MATING PART AND APPLY LOCTITE 425.
- $\cancel{15}$ AS SPECIFIED.
- 16 MAY BE SUPPLIED WITH STORZ FITTING WHEN SPECIFIED.
- $\cancel{17}$ OPTIONAL DRAIN VALVE LOCATION, USE PERMABOND LH050 OR LOCTITE 592.
- 18 TIGHTEN TO 50-55 IN-LBS.

Parts List Sheet:

124912

D47460



have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products. © 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, **ONLINEREPAIR.AKRONBRASS.COM**

Chg. Date 08 08-17 09 10-17

USE PARKER O-LUBE ON ALL

ASSEMBLY NOTES:

O-RINGS AND MATING SURFACES

- UNLESS OTHERWISE NOTED.
- /1\ USE PERMABOND LM113 OR LOCTITE 222.
- 2 USE MOBILITH SHC 460.
- /3\ DIMPLE AT ASSEMBLY.
- 6 ALIGN BALL IN HOLE. TIGHTEN PLUG UNTIL TOUCHES BALL. THEN BACK OUT PLUG 1/4-1/2 TURN.
- TIGHTEN UNTIL SLIGHT DRAG IS ON ITEM (42)
- /9\ TIGHTEN UNTIL ALL END PLAY IS ELIMINATED. SHAFT ASSEMBLY MUST STILL SPIN FREELY. DO NOT OVERTIGHTEN.
- <u>10</u> USE LOW-TEMP LUBRIPLATE.
- /1 Use Never Seez Mariners Choice.
- △ L USE PRIMER T AND PERMABOND HH120 OR LOCTITE 277.
- <u>∕1</u>3 USE PARKER O-LUBE.
- 14 THOROUGHLY CLEAN THREADS OF PLUG AND MATING PART AND APPLY LOCTITE 425.
- $\cancel{15}$ AS SPECIFIED.
- 16 MAY BE SUPPLIED WITH STORZ FITTING WHEN SPECIFIED.
- $\triangle \uparrow \land$ OPTIONAL DRAIN VALVE LOCATION, USE PERMABOND LH050 OR LOCTITE 592.
- 18 TIGHTEN TO 50-55 IN-LBS.

(68)

(67

(78)

(74)

Parts List Sheet:

124912



TECHNICAL SERVICE PARTS

STYLE 7982, 7983

PRODUCT INTAKE VALVE

| Find | | Description | ltem | QTY | Find | Description | Item | QTY |
|------|-------|---|--------|-----|------|---------------------------------------|--------|-----|
| 1 | | VALVE BODY 5.5" SWIVEL STYLE 7982 - PAINTED RED | 126483 | 1 | 25 | GEAR | 718314 | 1 |
| 1 | | VALVE BODY 5" BSP STYLE 7983 - PAINTED RED | 126484 | 1 | 26 | WOODRUFF KEY 213 SS | 727071 | 1 |
| 2 | | BALL ST. STL. | 803173 | 1 | 27 | BEARING .75 ID | 803176 | 1 |
| 3 | ## | O-RING 2-260 | - | 1 | 28 | SHAFT | 770404 | 1 |
| 4 | * * * | BALL 1/4" ST. STL. | - | 242 | 29 | WASHER | 784251 | 4 |
| 5 | | SWIVEL ADAPTER | 702236 | 1 | 30 | NUT HEX LOCK 3/8-16 | 734093 | 1 |
| 6 | ##, @ | SEAL BALL | - | 1 | 32 | O-RING 2-210 | 757226 | 3 |
| 7 | @ | RETAINER RING 5-3/4" INTERNAL | 758351 | 1 | 33 | WASHER THRUST | 784104 | 2 |
| 8 | * * | PLUG SWIVEL | - | 3 | 34 | TRUNNION | 124919 | 1 |
| 9 | ### | SWIVEL 6"NH LH | 104053 | 1 | 36 | GEAR SECTOR LH | 718316 | 1 |
| 9 | ### | SWIVEL 5"NH RL | 110081 | 1 | 37 | CAP GEAR | 125848 | 1 |
| 9 | ### | SWIVEL 6"NH 4RL | 104019 | 1 | 38 | SCREW PAN HEAD 5/16-18 x 5/8 | 765368 | 4 |
| 10 | ## | GASKET RUBBER 6" | - | 1 | 39 | INDICATOR | 124916 | 1 |
| 10 | ## | GASKET RUBBER 5" | - | 1 | 40 | WASHER | 784252 | 1 |
| 11 | | SCREW SOCKET NYLOCK SET 1/4-20 x 5/16" | 766015 | 3 | 41 | SCREW BUTTON HEAD 8-32 x 1/2" | 765370 | 1 |
| 12 | | HANDWHEEL | 124906 | 1 | 42 | VALVE HANDLE | 124918 | 1 |
| 13 | * * * | O-RING 2-254 | 757491 | 1 | 43 | O-RING 2-111 | 757269 | 1 |
| 14 | * * * | 30 DEGREE ELBOW - PAINTED RED | 126485 | 1 | 44 | RETAINER SEAT | 124915 | 1 |
| 15 | | STORZ ADAPTER 5"/125MM W/LOCK, SEAL, GASKET | 107071 | 1 | 45 | BRASS WASHER | 784034 | 1 |
| 15 | | STORZ ADAPTER 4"/100MM W/LOCK, SEAL, GASKET | 116986 | 1 | 46 | SEAT | 770424 | 1 |
| 16 | * * * | PLUNGER RETRACTABLE SPRING | 745259 | 1 | 47 | SPRING WASHER | 770423 | 4 |
| 17 | | O-RING 2-207 | 757217 | 1 | 48 | SCREW HEX SOCKET BUTTON 3/8-16 x 1/2" | 767159 | 1 |
| 18 | | TRUNNION THREADED | 772224 | 1 | 49 | WASHER 3/8 | 784126 | 1 |
| 19 | | ID PLATE | 745279 | 1 | 50 | SEAT | 768457 | 1 |
| 20 | | SCREW SOCKET BUTTON HEAD CAP 1/4-20 x 3/8 | 767190 | 2 | 51 | RELIEF PLUNGER | 124922 | 1 |
| 21 | | SCREW SOCKET FLAT HEAD CAP #10-24 x 3/8 | 763065 | 2 | 52 | O-RING 2-222 | 757006 | 2 |
| 22 | | DUST CAP | 126011 | 1 | 53 | O-RING 2-231 | 757126 | 1 |
| 23 | | WASHER UHMW | 784250 | 2 | 54 | SPRING | 770422 | 1 |
| 24 | | BEARING .50 ID | 803175 | 1 | 55 | RELIEF BODY | 124917 | 1 |
| | | | | | 56 | RELIEF ADJUSTMENT NUT | 124911 | 1 |

* THE INLET AND OUTLET BOTH USE BALL BEARING SWIVELS. THE QUANTITY USED IS AS FOLLOWS: 3" INLET FEMALE - 47 4" INLET FEMALE - 58 4.5" INLET FEMALE - 69 5" INLET FEMALE - 72 4" INLET STORZ - 54 5" INLET STORZ - 61 5" OR 6" OUTLET SWIVEL - 88

** KIT OF 50 BALLS: 123074, INCLUDES ITEM 8 (1x). *** 7982 ONLY. # OPTIONAL DRAFTING GASKETS FOR STORZ 4" P/N - 714211 5" P/N - 714212 6" P/N - 714213 ## FOR ITEMS 3, 6, 10 ORDER REPAIR KIT 91690001,@ ### FOR OTHER THREADS ORDER BY DESCRIPTION AND THREAD SIZE (ODM & TPI) OR BY AKRON THREAD CODE.

PHONE: 330.264.5678 or 800.228.1161 | FAX: 330.264.2944 or 800.531.7335 | www.akronbrass.com


WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Scene Star Lights carry a (6) year warranty. Weldon products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.


© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, **ONLINEREPAIR.AKRONBRASS.COM**

Chg. Date 08 08-17 09 10-17







Parts List Sheet:

124912



TECHNICAL SERVICE PARTS

STYLE 7982, 7983

PRODUCT INTAKE VALVE

| Find | | Description | Item | QTY |
|------|---------------------|---|--------|-----|
| 61 | WASHER THICK | | 784253 | 1 |
| 62 | WASHER LARGE O.D. | | 784254 | 1 |
| 63 | CAP STORZ 4"W/CHAIN | | 707359 | 1 |
| 63 | CAP STORZ 5"W/CHAIN | | 707360 | 1 |
| 63 | | CAP STORZ 6"W/CHAIN | 707373 | 1 |
| 64 | LABEL BLEEDER VALVE | | 729812 | 1 |
| 65 | | PLUG 1/4 NPT | 744011 | 1 |
| | | DRAIN VALVE | 779096 | 1 |
| 68 | | GASKET 5" BSP | 714209 | 1 |
| 73 | ### | INLET ADAPTER 4"NH/M | 116895 | 1 |
| 67 | ### | INLET ADAPTER 4.5"NH/M | 116891 | 1 |
| 67 | ### | INLET ADAPTER 5"NH/M | 116892 | 1 |
| 67 | ### | INLET ADAPTER 6"NH/M | 116893 | 1 |
| 75 | | WASHER FLAT | 784256 | 1 |
| | | INLET SWIVEL ADAPTER 3"BB | 126045 | 1 |
| 76 | ### | SWIVEL 3"NH 3RL | 104013 | 1 |
| | | GASKET 3" | 714022 | 1 |
| | | INLET SWIVEL ADAPTER 4"BB | 116886 | 1 |
| 76 | ### | SWIVEL 4"NH LH | 104049 | 1 |
| | | GASKET 4" | 714024 | 1 |
| | | INLET SWIVEL ADAPTER 4.5"BB | 116888 | 1 |
| 76 | ### | SWIVEL 4.5"NH 4RL | 104016 | 1 |
| 76 | ### | SWIVEL 4.5"NH LH | 104050 | 1 |
| | | GASKET 4.5" | 714025 | 1 |
| | | INLET SWIVEL ADAPTER 5"BB | 116889 | 1 |
| 76 | ### | SWIVEL 5"NH 4RL | 104017 | 1 |
| | | GASKET 5" | 714026 | 1 |
| | | INLET SWIVEL ADAPTER 4"STORZ | 116887 | 1 |
| 77 | | O-RING 2-243 | 757337 | 1 |
| | # | SWIVELING STORZ ADAPTER 4"/100MM W/LOCK, SEAL, GASKET | 713205 | 1 |
| | | INLET SWIVEL ADAPTER 5"STORZ | 116890 | 1 |
| 77 | | O-RING 2-247 | 757078 | 1 |
| | # | SWIVELING STORZ ADAPTER 5"/125MM W/LOCK, SEAL, GASKET | 713206 | 1 |
| 70 | | INLET ADAPTER 6"STORZ | 116896 | 1 |
| 78 | # | STORZ ADAPTER 6"/150MM W/LOCK, SEAL, GASKET | 116897 | 1 |

PHONE: 330.264.5678 or 800.228.1161 | FAX: 330.264.2944 or 800.531.7335 | www.akronbrass.com

WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Scene Star Lights carry a (6) year warranty. Weldon products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.

© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, ONLINEREPAIR.AKRONBRASS.COM

| Chg. | Date |
|------|-------|
| 08 | 08-17 |
| 09 | 10-17 |

Parts List Sheet:

124912

D47460