



## PROTAC® 2.0 RAIL MOUNT

- DESCRIPTION:** The ProTac® 2.0 Rail Mount is a 2,000-lumen tactical weapon-mounted flashlight that uses a proprietary Streamlight SL-B50® protected Li-Ion rechargeable battery pack. The ProTac® 2.0 Rail Mount features a tactical tail cap switch and a remote pressure switch for momentary or constant on operation and three different user-selectable programs. The Streamlight SL-B50® charges directly via USB-C port in the body of the battery. The battery is keyed to ensure proper alignment of the charging port. USB-C cord included.
- CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.
- DIMENSIONS:** Length: 6.30 in (160 mm)      Head Diameter: 1.46 in (37 mm)      Body Diameter: 1.02 in (26 mm)
- WEIGHT:** 9.06 oz (257 g) with (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery (included in purchase)
- LENS:** Glass with anti-reflective coating; gasket-sealed
- LIGHT SOURCE:** LED technology, impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** See chart. Fully regulated output for consistent lumen performance over the entire battery life
- ON/OFF:** Multi-function, push-button tail switch with momentary and latching constant on operations. Optional remote switch available in momentary only and momentary/latching versions. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high.
- RUN TIME:** See chart. All run time claims are to 10% of initial lumen output.
- BATTERY:** One (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery pack with on-board safety control, 4,900mAh. Recharges in 6 hours.

**FEATURES:**







- LED technology for extreme brightness
- IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
- All openings O-ring sealed
- 2-meter impact resistance tested
- Securely fits a broad range of weapons
- Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK compatible rail systems
- Extensively live fire tested, impact-resistant construction
- Serialized for positive identification

- APPROVALS:**  Meets applicable United Kingdom and European Community Directives  
 CEC Compliant

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** USB-C charge cord, remote pressure switch, SL-B50® battery pack

**OUTPUT:**

FL 1 Standard	HIGH	LOW
	2000 LUMENS	250 LUMENS
	2h 30min	11h
	266m	93m
	17,700cd	2,150cd

Strobe Run Time: 4h 30min