

Enforcer

PORTABLE CAFS TECHNOLOGY



MODEL	ENFORCER 3 SUPER DUTY	ENFORCER 3 BACK PACK	ENFORCER 10	ENFORCER 30 SKID
PRE-MIX CAPACITY	3 US Gallons	3 US Gallons	10 US Gallons	30 US Gallons
FINISHED FOAM CAPACITY	60 US Gallons	60 US Gallons	200 US Gallons	600 US Gallons
THROW DISTANCE	45 Feet	45 Feet	45 Feet	45 Feet
DISCHARGE DURATION	1 Minute	1 Minute	2:30 Minutes	3 Minutes
DISCHARGE HOSE	4 Ft. x 3/8" Booster	4 Ft. x 3/8" Booster	70 Ft. 1/2 x 1/2" Booster	70 Ft. x 1/2" Booster
HEIGHT	22.5"	22.5"	22"	32"
WIDTH	13"	13"	22"	21"
LENGTH	8.25"	8.25"	26"	42"
EMPTY WEIGHT	23 lb	23 lb	95 lb	136 lb
LOADED WEIGHT	48 lb	48 lb	175 lb	388 lb
CERTIFICATIONS			UL 711 20:B	UL 711 10:A, 60:B



MODEL	ENFORCER 60	ENFORCER 60 SKID	ENFORCER 200
PRE-MIX CAPACITY	60 US Gallons	60 US Gallons	200 US Gallons
FINISHED FOAM CAPACITY	1 200 US Gallons	1 200 US Gallons	4000 US Gallons
THROW DISTANCE	95 Feet	95 Feet	120 Feet
DISCHARGE DURATION	6 Minutes	6 Minutes	20 Minutes
DISCHARGE HOSE	50 Ft. x 1" Lay Flat	50 Ft. x 1" Lay Flat	300' x 1" Booster 50Ft. x 1.5" Lay Flat
HEIGHT	38.5"	30.5"	45"
WIDTH	42"	35"	44"
LENGTH	54.5"	50"	98"
EMPTY WEIGHT	485 lb	238 lb	1 200 lb
LOADED WEIGHT	985 lb	747 lb	2800 lb
CERTIFICATIONS	UL 711 10:A, 60:B	UL 711 10:A, 60:B	UL 711 10:A, 60:B