

HSB74 | Stack Bag

Specifications			
article number			151.000.950
model			HSB74
max. working pressure	psi		174
short description			Stack Bag
max. working pressure	bar		12
max. lifting capacity	lbf		162762
max. inflation height	in		6.7
thickness incl. profile	in		1.1
max. lifting capacity (12 bar/174 psi)	lbf		162762
max. lifting capacity (8 bar/116 psi)	lbf		108583
lifting capacity at insertion height plus 25 mm / 1 in. (12 bar /174 psi)	lbf		147924
lifting capacity at insertion height plus 25 mm / 1 in. (8 bar /116 psi)	lbf		98691
lifting capacity at max. lifting height (12 bar/174 psi)	lbf		83179
lifting capacity at max. lifting height (8 bar/116 psi)	lbf		55303
air content (12 bar/174 psi)	gal		220.1
air content (8 bar/116 psi)	gal		146.6
min. bursting pressure	psi		696
connection			ISO 6150 C
material			reinforced with 2 aramide inlays
weight, ready for use	lb		52.5
dimensions (AxBxC)	in		33.1 x 33.1 x 1.1
temperature range	°F		-4 + 131
EN 13731 compliant			yes
NFPA 1960 compliant			yes

- Standard supplied with**
- Carrying straps
 - Flexible integrated dust cap on air inlet

Accessories	
Air Adapter Set AAS 12	151.000.223
Triple retaining strap (set of 4 pcs)	151.001.194
T-splitter TS12	151.004.864
Air Control Set ACS 12	350.182.125
Connection Piece	350.582.430

