



# SPECIFICATION SHEET

## 16-377



### G-TEK® POLYKOR® X7™ SEAMLESS KNIT POLYKOR® X7™ BLENDED GLOVE WITH NEOFOAM® COATED PALM & FINGERS - TOUCHSCREEN COMPATIBLE

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell with X7™ technology offers very high cut resistance and durability with ultra-thin liners
- NeoFoam® coated palm and fingertips offers great abrasion resistance and outstanding wet/dry grip
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light
- Complies with FDA food handling requirements 21 CFR 177.2600
- Meets EN 1149 for protective clothing electrostatic properties

### APPLICATIONS

- Finishing & inspection
- Electronics
- General duty
- Small parts assembly
- Construction
- Maintenance

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

### TECHNICAL DATA

MATERIAL	PolyKor® with X7™ Technology / NeoFoam® Coating				
CONSTRUCTION	18 Gauge seamless knit				
COLOR	Shell: ■ Black / Coating: ■ Black				
SIZES	S - XXL				
PACKAGING	1 pair per bag, 12 pairs per dozen, 6 dozen per case				
CASE DIMENSIONS	15" x 12.2" x 11.4" / 38cm x 31cm x 29cm				
CASE WEIGHT	S	M	L	XL	XXL
	9.9 lbs	10.1 lbs	10.6 lbs	11.5 lbs	12.3 lbs
	4.5 kgs	4.6 kgs	4.8 kgs	5.2 kgs	5.6 kgs
COO	China				



### BARCODES


ITEM	BAG	DOZEN	CASE
■ 16-377/S	616314245602	01616314245601	02616314245600
■ 16-377/M	616314245619	01616314245618	02616314245617
■ 16-377/L	616314245626	01616314245625	02616314245624
■ 16-377/XL	616314245633	01616314245632	02616314245631
■ 16-377/XXL	616314245640	01616314245649	02616314245648

### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
<b>A</b>	9 / 23	9.4 / 24	9.8 / 25	10.2 / 26	10.6 / 27
<b>B</b>	3.6 / 9.2	3.7 / 9.5	4 / 10.3	4.1 / 10.6	4.3 / 10.8
<b>H</b>	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

### PERFORMANCE PROPERTIES

<b>EN388: 4X42F</b>	ASTM F2992-15 ANSI Cut Level A7 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (TDM-100)	A	B	C	D	E	F



**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobal.com](http://www.pipglobal.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.