

SL-20L® / SL-20LP®
FULL SIZE RECHARGEABLE LED FLASHLIGHT

MARKET
APPLICATIONS: Law Enforcement, Fire & Rescue, Utility, Security, Automotive, Industrial, Sporting Goods, Consumer

DESCRIPTION: Feature packed, the SL-20L® and SL-20LP® full sized professional grade, high-intensity, rechargeable flashlights offer 3 microprocessor controlled variable intensity modes, strobe mode and the latest in power LED technology. The combination of rechargeable batteries and high power LED results in one of the lowest operating costs of any full size flashlight made.

CASE MATERIAL: **SL-20L®:** Machined aircraft-grade aluminum with type II anodized finish. Available in black.
SL-20LP®: Lightweight, impact resistant nylon polymer case designed with non-slip rubber comfort grip. Available in high visibility yellow, safety orange or non-glare black.

DIMENSIONS: **SL-20L®** Length: 13.1 in. (33.3 cm) Diameter: Major Diameter: 2.50 in. (6.35 cm)
SL-20LP® Length: 13.2 in. (33.5 cm) Body Diameter: 1.50 in. (3.81 cm)

WEIGHT: **SL-20L®:** 1.7 lb. (.77 kg) with battery **SL-20LP®:** 1.3 lb. (.59 kg) with battery

LENS: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity. Deep-dish parabolic reflector produces a tight beam with optimal peripheral illumination to aid in navigation.

ON/OFF: Multi-function, push-button barrel switch. One handed operation of momentary, variable intensity or strobe mode.

RUN TIME: See chart. All claims to 10% of initial lumen output. Strobe: 4.5 continuous hours.

BATTERY: 5-cell, 6.0 Volt, 2.6Ahr Ni-MH sub-C battery, rechargeable up to 1000 times.

CHARGING: Fits existing charger-holders and fully recharges within 9 hours. Illuminated switch housing indicates charge status; steady for charging and blinking for charging complete.

CHARGE CORDS: Streamlight universal AC input voltage, 12.7V/.8A output charge cords available with IEC Type A (US & Japan), Type C (Euro), Type G (UK) or Type I (Australia) plugs. 12VDC cigarette lighter or direct wire automotive cords.





FEATURES: High power LED for extreme brightness.
 IPX4 rated design; water resistant operation.
 1 meter impact resistance tested.
 Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:  Meets applicable European Community Directives.

 CEC Compliant

OPTIONAL ACCESSORIES: Safety wands, 5-Unit Back Charger, Ring holder and Holster.

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		450 LUMENS	225 LUMENS	60 LUMENS
RUNTIME		3h 15min	5h	20h
DISTANCE		529m	374m	189m
INTENSITY		70,000cd	35,000cd	9,000cd

Strobe runtime: 4.5 hours

SL-20L / SL-20LP PERFORMANCE CURVE

