

HLB 2 | Lifting Bag

| Specifications | | | |
|--|-----|--|----------------------------------|
| article number | | | 350.321.021 |
| model | | | HLB 2 |
| max. working pressure | psi | | 174 |
| short description | | | Lifting Bag |
| max. working pressure | bar | | 12 |
| max. lifting capacity | lbf | | 4721 |
| max. inflation height | in | | 3.7 |
| thickness incl. profile | in | | 0.9 |
| max. lifting capacity (12 bar/174 psi) | lbf | | 4721 |
| max. lifting capacity (8 bar/116 psi) | lbf | | 3147 |
| air content (12 bar/174 psi) | gal | | 2.5 |
| air content (8 bar/116 psi) | gal | | 1.7 |
| water content | gal | | 0.2 |
| min. bursting pressure | psi | | 696 |
| connection | | | ISO 6150 C |
| material | | | reinforced with 3 aramide inlays |
| weight, ready for use | lb | | 1.5 |
| dimensions (AxBxC) | in | | 7.9 x 6.3 x 0.9 |
| temperature range | °F | | -4 +131 |
| EN 13731 compliant | | | yes |

- Standard supplied with**
- Flexible integrated dust cap on air inlet

| Required Accessories | |
|----------------------------|-------------|
| Control Unit HDC 12 | 350.182.095 |
| Shut-Off Hose SOH 12 | 350.182.096 |
| Pressure Reducer PRV 12 | 350.182.100 |
| Air Hose AH 5 Y | 350.570.022 |
| Air Hose AH 5 B | 350.570.023 |
| Air Hose AH 10 B | 350.570.026 |
| Air Hose AH 10 Y | 350.570.027 |
| Air Hose AH 5 O | 350.570.030 |
| Air Hose AH 10 O | 350.570.031 |
| Pressure Reducer PRV 12 LP | 358.182.000 |
| Pressure Reducer PRV 12 HP | 358.182.001 |
| Shut-Off Hose SOH 174 | 358.570.007 |
| Air Bottle 300 Bar | 350.581.096 |
| Air Hose AH 16 YW | 358.570.001 |
| Air Hose AH 16 DB | 358.570.002 |
| Air Hose AH 16 RD | 358.570.003 |
| Air Hose AH 32 RD | 358.570.004 |
| Air Hose AH 32 DB | 358.570.005 |
| Air Hose AH 32 YW | 358.570.006 |

