



E-FLOOD® LITEBOX® HL HIGH LUMEN RECHARGEABLE LANTERN



Material/Lens High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle. Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed

Dims/Weight Length: 12.3 in. (31 cm) Body Width: 5.1 in. (13 cm) Overall Height: 7.7 in. (19 cm); 10.4 lbs (4.7 kg) with battery

Light Source/ Output/Runtime Six white LEDs and wide pattern reflectors produce a uniform flood pattern with two selectable beam widths and three light output intensities:
 - High for a super-bright flood beam: 5,300 lumens, 42,000 candela, 410m beam distance, runs 1.75 hours
 - Medium for an intense beam and longer run time: 2,500 lumens, 21,300 candela, 292m beam distance, runs 4.5 hours
 - Low extended run time: 1,300 lumens, 11,600 candela, 215m beam distance, runs 10 hours

Switch Toggle switch

Battery Zero-maintenance 12V, 7.2Ah sealed lead acid battery

Features - Selectable diffuser settings for two beam widths. Works with all three modes
 - 90° swivel neck allows you to aim the beam where you need it for optimum task lighting

Models Standard System - International safety orange; includes shoulder strap AC/DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites, and remote equipment

Vehicle Mount System - International safety orange; comes with vehicle-mountable hard-wire rack and shoulder strap

Approvals Most models meet applicable European Community Directives.
 Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Description	UPC	Item #
E-Flood LiteBox HL Standard System - 230V AC/12V DC - shoulder strap & mounting rack - Orange	080926-45662-4	45662
E-Flood LiteBox HL Standard System - 240V AC/12V DC - shoulder strap & mounting rack - Orange	080926-45663-1	45663
E-Flood LiteBox HL Standard System - 120V/100V AC/12V DC - shoulder strap & mounting rack - Orange	080926-45661-7	45661
E-Flood LiteBox HL Vehicle Mount System - 12V DC - shoulder strap, - Orange	080926-45665-5	45665
E-Flood LiteBox HL (WITHOUT CHARGER) - Orange	080926-45660-0	45660

Assembled in USA

	Description	UPC	Item #
	DC2 direct wire charge cord	080926-22050-8	22050
	DC1 Charge Cord	080926-22051-5	22051
	12V DC power cord 10ft (3 meters)	080926-22056-0	22056
	120V/100V Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22085-0	22085
	230V Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22061-4	22061
	240V [UK] Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22062-1	22062
	240V [AUS/NZ] Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22048-5	22048
	Locking Device (keyed differently) *Must be factory installed	080926-40163-1	40163
	Quick Release Strap	080926-44050-0	44050
	Shoulder Strap	080926-45232-9	45232
	Standard System Mounting Rack Orange	080926-45070-7	45070
	Direct Wire 12V DC Mounting Rack** Orange	080926-45071-4	45071
	Battery - HID LiteBox/E-Flood LiteBox HL	080926-45630-3	45630