

Dusk

710-401 (110v) 710-404 (230V)

Features

- 1000 watt extruded aluminum heat exchanger
- Continuous fog output with auto-ramping
- Simple On/Off control switch
- Rear mounted for virtually maintenance free operations (regular cleaning only)

Specifications

Output: 1L/h of Smoke Fluid Power: 9.1A @ 110V/60 Hz

4.3A @ 230V/50Hz

Weight: 11.9 lbs

Dimensions: 16.0 x 7.5 x 8.2 inch

Houseing: Rugged 12 gauge steel case

Chip resistant powder-coated paint

Hard point attachments for hanging

Approvals: CE

RoHS Compliant

ETL / cETL (Pending)

Warranty: 1 Year





NIGHT FALL



Nightfall

710-430 (110v) 710-435 (230v)



- 1200 watt heat exchanger
- 7 Minute start-up time
- Direct thermal protection
- Rear mounted XLR socket (provides 12V DC at 50mA) to power and interface device for triggering the machine. (eg. remote control).
- Removable digital remote control with 9.8 foot cable
- Adjustable flow rate
- Permanent heating system
- Programmable emission

Specifications

Output: 21,190 ft3/min Flowrate in

continuous low-flowrate operation

See. 2

Power: 1050W, 8.75A @ 110V 60 Hz

Weight: 24.7 lbs

Capacity of built-in

tank: 0.66 Gallon/2.5 liters

Fluid consumption: 0.02 Gal/min

Dimensions: 19.1 x 13.2 x 9.6 inch

Warranty: 5 Years



BLACKOUT



Blackout

710-431 (110v) 710-436 (230v)



Features

- 2100 watt heat exchanger
- 10 Minute start-up time
- Direct thermal protection
- Rear mounted XLR socket (provides 12V DC at 50mA) to power and interface device for triggering the machine. (eg. remote control).
- Removable digital remote control with 9.8 foot cable
- Adjustable flow rate
- Permanent heating system
- Programmable emission

Specifications

Output: 46,615 ft3/min Flowrate in

continuous low-flowrate operation

Power: 1800W, 15A @ 110V 60 Hz

Weight: 39.1 lbs

Capacity of built-in

tank: 1.32 Gallon/5 liters Fluid consumption: 0.05 Gal/min

Dimensions: 23.1 x 15.6 x 12.1 inch

Warranty: 5 Years