

SURVIVOR® X

DESCRIPTION: The Survivor® X is an intrinsically safe, lightweight, handheld flashlight with a right-angle head designed for use in hazardous locations. This light features a low-profile bezel length to minimize snag hazards. A large translucent button with an LED battery indicator provides gloved access to microprocessor-controlled high and low intensity modes and emergency flash. Optional Smoke Cutter® optic technology offers insertable black or amber plugs for user-customizable beam pattern.


CASE MATERIAL: Housing, base and battery housing made from high-impact, super tough nylon offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in international safety orange and high visibility yellow.

DIMENSIONS: Height: 7.06 in. (17.92 cm) Width: 2.85 in. (7.24 cm) Diameter: 2.32in. (5.89 cm)
 Height in charger: 8.67 in. (22.02 cm)
 Grip area: Height: 3.60 in. (9.14 cm) Width: 2.20 in. (5.59 cm) Thickness: 1.35 in. (3.43cm)

WEIGHT: Li-Ion: 12.2 oz (346 grams) * Alkaline: 12.8 oz (363 grams) * SL-B26: 11.9 oz (337 grams) *

LENS: Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.



Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination. Optional insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.

ON/OFF: Ultrasonic welded push-button switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation even when wearing heavy gloves.

RUN TIME: See chart. All claims to 10% of initial lumen output. Flash: 8 hrs continuous.

BATTERY: 2.6Ah Li-Ion battery pack rechargeable up to 1,000 times available with 120/230/240VAC systems. Fully charges in 5 hours. Charger indicator turns red when charging, turns green when fully charged. One (1) optional Streamlight SL-B26® protected Li-Ion USB-rechargeable battery pack. Three (3) optional "AA" alkaline batteries.

BATTERY STATUS INDICATOR: The translucent switch boot contains an integrated red/green battery status indicator.
 Solid green for 5 seconds: Battery is ready for use
 Solid red: 45 minutes or less of battery life remaining
 Flashing red: 15 minutes or less of battery life remaining

FEATURES:



Updated battery door design for improved operation and seal
 Translucent switch boot with integrated battery status indicator
 Updated charge cradle for one-handed light removal
 Multi-fuel design
 IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
 2-meter impact resistance tested
 Serialized for positive identification

APPROVALS:**



Class I & II, Division 1, Groups A,B,C,D,E,F,G; Class III, T-Code: T3/T4
 T-CLASS T4 only: Streamlight 90341, Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91/L91
 T-CLASS T3 only: Streamlight 90340, Energizer E91, Rayovac No. 815
 Class I & II, Division 2, Groups A,B,C,D,F,G; Class III, T-Code: T4 only with Streamlight 220115

** See product for specific ratings.



Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013).
 Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position.



CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES:

5-Unit Bank Charger
 Li-Ion Battery

Alkaline Batteries

SL-B26® USB Battery

	FL1 STANDARD	HIGH	LOW
OUTPUT	250 LUMENS	60 LUMENS	60 LUMENS
RUNTIME	3h 45min	15h	15h
DISTANCE	447m	237m	237m
INTENSITY	50,000cd	14,000cd	14,000cd

	FL1 STANDARD	HIGH	LOW
OUTPUT	250 LUMENS	60 LUMENS	60 LUMENS
RUNTIME	5h	15h	15h
DISTANCE	447m	237m	237m
INTENSITY	50,000cd	14,000cd	14,000cd

	FL1 STANDARD	HIGH	LOW
OUTPUT	250 LUMENS	60 LUMENS	60 LUMENS
RUNTIME	4h	15h	15h
DISTANCE	447m	237m	237m
INTENSITY	50,000cd	14,000cd	14,000cd

* With battery (based on model; included in purchase)

All performance claims tested to ANSI/PLATO FL1-2019 Standard