

# POWER BLOWERS™

Electric



## Single-Speed Electric Power Blowers™

Tempest **Single-Speed** PPV fans feature some of the lightest designs available and are perfect for departments looking to go electric on a limited budget. Available with hazardous location (Explosion Proof, EP) motors which are intended for Class 1, Group C&D and Class 2 Group F&G environments. Motors can be ordered in 110-120V/60Hz or 220-230V/50Hz. (110-120V part numbers shown; call for 220-230V part numbers)

Model No.	Part No.	Size	HP	CFM	Dimensions (WxDxH)	Weight
SS-16-S-1.5	910-1200	16"	1.5	11,804	20.50" x 19.75" x 21.75"	74 lbs.
SS-18-S-1.0	910-1220	18"	1.0	8,748	22.00" x 21.00" x 24.25"	76 lbs.
SS-21-S-1.0	910-1240	21"	1.0	11,698	24.75" x 21.00" x 26.25"	81 lbs.
SS-24-S-1.0	910-1260	24"	1.0	12,867	28.00" x 21.00" x 30.00"	90 lbs.



## VSG Variable-Speed Electric Power Blowers™

The **VSG Power Blower™** is the perfect balance in electric driven performance, variable speed control and value. All models feature a powerful 1.5 HP motor and simple to operate 0 to 100 variable speed control. NEMA-4 rated drive provides extra protection in wet environments. This fan will operate on GFCI protected circuits.

Model No.	Part No.	Size	HP	CFM	Dimensions (WxDxH)	Weight
VS-16-G-1.5	910-1300	16"	1.5	11,125	21.00" x 19.75" x 21.75"	89 lbs.
VS-18-G-1.5	910-1320	18"	1.5	11,861	23.00" x 21.00" x 24.25"	95 lbs.
VS-21-G-1.5	910-1340	21"	1.5	13,414	26.00" x 21.00" x 26.25"	99 lbs.
VS-24-G-1.5	910-1360	24"	1.5	12,901	29.50" x 21.00" x 30.00"	109 lbs.



## VSR Variable-Speed Electric Power Blowers™

The **VSR** is the latest innovation in our variable speed electric offering and delivers unmatched performance, bridging the gap between gas and electric airflow. All models feature a class leading 2.0 HP motor and simple to operate 0 to 100 variable speed control. NEMA-4 rated drive provides extra protection in wet environments. This fan will operate on GFCI protected circuits. Motors can be ordered in 110-120V/60Hz or 220-230V/50Hz. (110-120V part numbers shown; call for 220-230V part numbers)

Model No.	Part No.	Size	HP	CFM	Dimensions (WxDxH)	Weight
VS-16-R-2.0	910-1400	16"	2.0	11,551	21.00" x 19.75" x 23.00"	98 lbs.
VS-18-R-2.0	910-1420	18"	2.0	12,839	23.00" x 21.00" x 24.25"	104 lbs.
VS-21-R-2.0	910-1440	21"	2.0	14,836	26.00" x 21.00" x 26.25"	108 lbs.
VS-24-R-2.0	910-1460	24"	2.0	15,663	29.50" x 21.00" x 30.00"	119 lbs.



\*For icon explanation, please see page 13.

SS 16" Models



SS 18" Models



SS 21" Models



SS 24" Models



VSG 16" Models



VSG 18" Models



VSG 21" Models



VSG 24" Models



VSR 16" Models



VSR 18" Models



VSR 21" Models



VSR 24" Models

