

# OPL Basic

## Effective systems for On Premise Laundry

Built to meet the simplest needs of an on-premise laundry, yet featuring SEKO's design know how, OPL Basic is easy to install, straightforward to use and has a low maintenance requirement. All of this in a design that ensures user safety and equipment reliability. The OPL Basic Series offers a wide range of single and/or two product timed systems for liquid and dry product applications. Chemical dosing is activated automatically by a signal from the washer or by manually pressing the membrane switch located on the front of the unit.



**OPL Basic L**  
Single peristaltic pump dosing system



**OPL Basic LL**  
Double peristaltic pump dosing system



**OPL Basic D**  
Single solenoid valve dosing system

## Features

Dip switches, trimmers and jumpers make calibration and programming quick and easy

Front cover opens to 90° degrees for easy access to connections

Prime switches for each product

Easy Installation - Simply connect the tubing and power supply

Easily mounted and removed with built in mounting brackets

No special tools required

All settings are made inside the cabinet to discourage tampering

Optional remote manual switch also available

## Dosing time

Accepts program run time 0 - 10 minutes. Easy calibration method of programming.

## Lock out time

Prevents repeat dispensing of product from 0 - 75 minutes with dip switch settings. When the lock out time expires, the pump or solenoid valve will restart, if signalled.

## Delay time

Using an internal trimmer, delay the start of the pump from 0 - 5 minutes. When the OPL Basic receives a signal, dispensing won't begin until after the programmed delay time.

## Alarms

Optional: LED and buzzer signals an empty product warning.