FIREBULL

F3 Fluorine Free Foam



PRODUCT INFO:

FIREBULL F3 Fluorine Free Foam is a seamless transition from AFFF products for fire departments. The most complete and user friendly firefighting agent produced in the world, FIREBULL eliminates all of the long-established issues of Class B foams: it will not clog, gum, or corrode foam systems or equipment. FIREBULL offers the simplicity of using one product to extinguish multiple classifications of fire, allowing fire departments and brigades to increase their stocking supply by using just one product that serves two purposes. Unlimited Shelf Life.

FIREBULL F3 holds third party verification of concentrate free from PFOS and other PFAS available on request.

APPLICATIONS

US/European Class A Fires Wood, Grass, Coal, Tires, Hay, Cotton, Cardboard, Initial Knockdown: 0.25%

Wetting Agent: 0.25%-1.0%. Reapply as needed.

Cars, Trucks, Heavy Equipment: 0.50% up to 1.0%

US Class B, European Class B/C Fires Non-Polar Solvents: Gasoline, Gasoline w/10% Ethanol, Jet A, JP4/5/8, Crude Oil, Diesel, Etc. 3% using 0.16gpm/ft² for 10-20 minutes. Reapply as needed.



FEATURES

Compatible with all regular and all standard equipment Excellent burnback protection Rapid cooling properties 1st F3 with vapor barrier properties Applicable for Training at 1%, 3%, and 6% for low, medium, and high expansion Effective with Fresh Water,

CURRENT TESTING

Successful 20:B rating with
Heptane fuel fire from Southwest
Research Labs uisng Enforcer 10
CAF system
Successful UL 162 testing with
Southwest Research Labs
Successful 711 1:B testing using
aerosol cans and heptane fuel.

Scheduled Testing UL 162 (early 2020) NFPA 18 A and B (2020) ICAO Level C (2020)

Associated Products



FIREBULL
CLASS A WETTING AGENT



FIREBULL TRAINING FOAM



ENFORCER 30 CAFS



ENFORCER 10 CAFS