



FS-FSP1215-G

Northstar Classic 15' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 34 in. (86 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 10 in. (2.1 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



FS-FSP1220-G

Northstar Classic 20' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant

Class
1
Anchor at or above dorsal D-ring



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 39 in. (99 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 4 in. (2.2 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



FS-FSP1230-G

Northstar Classic 30' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 37 in. (94 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 1 in. (2.2 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



FS-FSP1250-G

Northstar Classic 50' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant

Class
1
Anchor at or above dorsal D-ring



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 5 in. (2.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



FS-FSP1265-G

Northstar Classic 65' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 35 in. (89 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 11 in. (2.1 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



FS-EX1080-G

Northstar Classic 80' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	8 ft. 5 in. (2.6 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized steel



FS-EX10-100-G

Northstar Classic 100' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant

Class
1
Anchor at or above dorsal D-ring



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	8 ft. 5 in. (2.6 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized steel

