

SM-PFP-20HPHND-MR

HONDA POWERED PRESSURE AND VOLUME PUMP

This pressure/volume pump is the most suitable for drop-in units. The engine and pump are mounted on skid frame. The skid version is easily mountable on vehicles and trailers.

Also available in portable version



ENGINE SPECIFICATIONS

- GX630 Honda air cooled engine
- V-Twin cylinder, 4-stroke gasoline engine
- Electric start
- Charge coil 12V-17A

PUMP UNIT SPECIFICATIONS

- C.E.T. single stage centrifugal pump
- Pump body made from high resistance aluminum alloy
- Bronze impeller
- Mechanical shaft seal
- Exhaust priming system, guaranteed up to 20' (6 meter) lift
- One 1 1/2" (38mm) delivery outlet
- One 2 1/2" (65mm) suction inlet
- Dimensions: Length: 19 3/4 (502 mm); Width: 24 1/4" (615 mm); Height: 24 3/4" (630 mm)
- Weight: 147.4 lbs (67 kg)


INCLUDED ACCESSORIES

- Pressure gauge
- Low oil alert
- Quick connect for 12-V battery

PERFORMANCE

MAX FLOW : 300 GPM
MAX PRESSURE : 205 PSI
240 GPM @ 50 PSI

180 GPM @ 100 PSI
125 GPM @ 150 PSI
60 GPM @ 200 PSI




LIMITED WARRANTY

- 3 YEARS



ACCEPT ONLY THE BEST



**A CENTURY
OF ENGINEERING
FOR THE BRAVEST**

75 Hector St., P.O. Box 90,
Pierreville (Québec)
Canada J0G 1J0
Phone : 1-800-567-2719
Fax : 1-800-434-2613
www.fire-pumps.com