



# X-Series Intrinsically Safe Flashlight with Multi-Angle Mount

**200**  
Lumens

- cETLus, ATEX, and IECEx listed Intrinsically Safe
- Beam distance rated at 143 meters
- Polymer housing
- Mount attaches to either side of the helmet



*This Flashlight is cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. Uses a CREE® LED rated at 200 lumens that works with a deep parabolic reflector to create a 143 meter flashlight beam. The tail switch provides momentary or constant-on functionality. Meets the requirements of NFPA-1971-8.6. Power comes from 3 AA premium batteries. The mount can be attached to either side of the helmet to provide hands-free illumination. Additionally, the user can set the angle of the mount through 140 degrees of adjustment to provide clearance around face shields, goggles or other helmet-mounted equipment.*

**INTRINSICALLY SAFE**



**XPP 5418GX-K01**







# X-Series Intrinsically Safe Flashlight with Multi-Angle Mount

## FEATURES

- cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Glass filled nylon polymer housing
- Non-slip grip
- Tail switch
- Mount can be attached to either side of helmet
- Mount allows for clearance around face shields, goggles or other helmet-mounted equipment.
- Dustproof / Waterproof
- Impact and chemical resistant
- Meets Requirements of NFPA-1971-8.6 (2013)
- 3 AA batteries (not included)
- Limited Lifetime Warranty

## SPECIFICATIONS

- Lumens: 200
- Run-time: 10.5 hrs
- Beam Distance: 143 meters
- Candela: 5129
- Water / Dust Rating: IP-67
- Drop Rating: 2 meters
- Dimensions: Length 5.6 in., Head Diameter 1.5 in., Handle Diameter .75 x 1.4 in., Weight 5.4 oz.

FL 1 STANDARD		
		
		

## SAFETY RATING

cETLus, ATEX, and IECEx listed Intrinsically Safe



Single tail switch



High-efficiency deep parabolic reflector



Clip Mount  
(mounts to either side of helmet)



Slot Mount  
(mounts to either side of helmet)

Model	UPC 0 17398
XPP-5418GX-K01	80620 6